


**SKYTEC™****TRC712****A LIGHTWEIGHT AND DURABLE NITRILE FOAM COATED GLOVE WITH MEDIUM CUT PROTECTION. MADE WITH RECYCLED POLYESTER**

TRC712 is an extremely durable and flexible glove offering a medium cut protection. The micro capillaries in the nitrile foam coating draw liquid away from the surface to ensure secure handling of sharp, slippery objects in oily and greasy conditions.

**FEATURES**

- › Cut resistant: Level C / ANSI A3
- › A flexible and comfortable glove offering great dexterity
- › HPPE on the inside provides comfort and protection
- › Foam nitrile coating gives exceptional grip while allowing warm air and moisture from inside to escape, keeping your hands dry and comfortable
- › Designed for easy movement and continuous wear
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › RCS (Recycled Claim Standard) certified
- › 1 pair = 1PET bottle of 500ml recycled
- › 25g of CO<sub>2</sub> reduced vs virgin polyester alternative

**SUITABLE FOR****Typical Industries**

- Automotive
- Construction
- Logistics
- Manufacturing
- Utilities

**Suitable Applications**

- Assembly
- Handling oily components with sharp edges
- Maintenance
- Light fabrication
- Precision Mechanics

**CERTIFICATION**

CAT II




EN 388:2016



4X43C

ANSI/ISEA 105



See overleaf for explanation

**GLOBUS**

**PRODUCTION INFORMATION**

<b>MATERIALS</b>	LINER:	13 gauge HPPE, glass fibre, recycled polyester
	COATING:	Foam nitrile
<b>COLOUR</b>	Orange/Black	
<b>LENGTH (mm)</b>	250 (Size Dependent)	
<b>CUFF STYLE</b>	Elasticated knit wrist	

**ORDERING DETAILS**

SIZE	CODE	PACKAGING
6/XS	SKG00014GB	10 pairs per paper wrap
7/S	SKG00014GD	
8/M	SKG00014GF	
9/L	SKG00014GH	
10/XL	SKG00014GJ	120 pairs per case
11/XXL	SKG00014GL	

**RECOMMENDATIONS FOR USE**

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement.
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight.
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

**CERTIFICATION LEGENDS****MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS\***

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

**CLASSIFICATION FOR CUT RESISTANCE**

Measured breakthrough time	Permeation performance index (grams)
A1	≥ 200
A2	≥ 500
A3	≥ 1000
A4	≥ 1500
A5	≥ 2200
A6	≥ 3000
A7	≥ 4000
A8	≥ 5000
A9	> 6000

**EUROPE**

[www.globusgroup.com](http://www.globusgroup.com)

**E:** [sales@globus.co.uk](mailto:sales@globus.co.uk)

**T:** +44 (0)161 877 4747

**F:** +44 (0)161 877 4746

**MIDDLE EAST & AFRICA**

[www.globusgroup.com/gcc](http://www.globusgroup.com/gcc)

**E:** [gcc@globusgroup.com](mailto:gcc@globusgroup.com)

**T:** +971 4 882 9962

**F:** +971 4 882 9963

**GLOBUS AMERICAS**

[www.globusgroup.com](http://www.globusgroup.com)

**E:** [americas@globusgroup.com](mailto:americas@globusgroup.com)